

10/519759

519,759

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
15 January 2004 (15.01.2004)

PCT

(10) International Publication Number
WO 2004/005647 A1

- (51) International Patent Classification⁷: **E04D 1/36**
- (21) International Application Number:
PCT/US2003/020627
- (22) International Filing Date: 1 July 2003 (01.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/393,396 2 July 2002 (02.07.2002) US
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant and
(72) Inventor: **HOFFMAN, Kenneth** [US/US]; 39017 Prentiss #206, Harrison TWP., MI 48045 (US).
- (74) Agent: **WEINTRAUB, Arnold, S.**; Plunkett & Cooney, P.C., 38505 Woodward Avenue, Suite 2000, Bloomfield Hills, MI 48304 (US).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: ROOF FLASHING STRIP AND METHOD OF PRODUCTION



(57) Abstract: A roof flashing strip (10) is formed by extruding or injection molding a suitable material of either plastic or metal. The roof flashing strip (10) is formed as an elongated member (16) which then can be cut to any suitable length. The roof flashing strip (10) includes a backing plate (14) having a plurality of legs (18, 18', 18'') projecting laterally outwardly therefrom and normal thereto. The legs (18) are inclined with respect to a horizontal plane (17) and vertically axially displaced such that there is a gap (24) therebetween, with portions of adjacent legs overlying and/or

underlying one another. The gap enables the emplacement of a shingle (30) thereinto.

WO 2004/005647 A1